

PRODUCT DATASHEET

FARGO PRINTER DTC1250

Highlights

ECONOMICAL

The best price-quality ratio for societies with simple needs

PRACTICAL

- Ribbons loading directly from the front in cartridge form.
- Cartridge-integrated cleaning roller.
- The ability to reprint already personalized badges.

Main features

- Available with or without encoder
- XF3 encoder compatible with MICROSESAME 2021 version and higher
- Loading bin for 100 badges



Electronic and graphic personalization

The Fargo DTC1250 ISO card printer is a high-performance entry-level color printer. Connected via USB to a MICROSESAME server or client workstation, it is coupled with the badge background edition, which manages the (photo, text, logo, etc ...) and RFID encoding.

Single or double-sided, the DTC1250 is very easy to use and guarantees fast printing : 16 seconds, badge with a color ribbon or 6 seconds/badge in monochrome printing.

With a resolution of 300 dpi and 16.7 million colors, dye-sublimation technology delivers photographic-quality, raster-free printing. And with specific (sensitized) cards, monochrome reprinting on already personalized badges is possible.

The compact DTC 1250 printer nonetheless incorporates a 100 cardhopper. It is available with or without Mifare encoding head.

INTEGRATED ACCESS CONTROL SYSTEM

AUTOMATES AND SPECIALIZED MODULES



EVOLUTION READER



BADGES, PRINTERS AND ACCESSORIES



FARGO PRINTER DTC1250

Dimensions

249 x 475 x 234 mm



References

- **IMPDTTC1250** : single-sided USB color printer
- **IMPDTTC1250-XF3** : single-sided USB color printer + encoder for MIFARE/DESFIRE* badges
- **IMPDTTC1250DS** : double-sided USB color printer
- **IMPDTTC1250DS-XF3** : double-sided USB color printer + encoder for MIFARE/DESFIRE* badges

* **XF3 encoder compatible with MICROSSAME version 2023.2 and higher**

- **IMPDTTC1000-RN** : black ribbon for Fargo DTC1250, 1000 faces
- **IMPDTTC1000-RC** : color ribbon for Fargo DTC1250, 250 sides
- **KIT-DTC1000** : cleaning kit for Fargo DTC1250



Technical details

- **Power supply** : 100-240 VAC - 1,6 A
- **Connexion** : USB
- **Loading bin** : 100 cards
- **Supported card formats** : PVC - 85,6 x 54mm - Thickness 0.229 à 1.016mm
- **Printing area** : 85,3 x 53,7mm
- **Display** : 300 dpi - 16,7 M of colors
- **Print speed** : 6 seconds (black) to 24 seconds (color)
- **Dimensions** : H 249 x L 475 x P 234 mm
- **Operating temperature** : +18°C to +27°C
- **Humidity** : 20 à 80% without condensation
- **Weight** : 4,54 kg

Complementary products

We offer a full range of badges and accessories, including rigid and flexible badge holders and lanyards. Please do not hesitate to contact us.



Sales contact: info@hirschsecure.fr
www.til-technologies.com